

ACT-Touch Reference Manual

Working Draft

Franklin P. Tamborello, II
Cogscent, LLC

Kristen K. Greene
National Institute of
Standards and Technology

Preface.....	3
Acknowledgments.....	4
Introduction.....	5
Loading ACT-Touch.....	7
Manual Request Extensions to ACT-R	8
Virtual Multitouch Display Device	12

Preface

This document describes the manual request extensions to ACT-R 6 (hereafter, ACT-R) provided by ACT-Touch as well as the included virtual multitouch display device. As ACT-Touch is intended to serve as an extension to ACT-R, this document follows the formatting conventions of the ACT-R Reference Manual by Dan Bothell. A description of that [notation](#) is quoted verbatim from that document for the reader's convenience. The scope of this manual is restricted to the ACT-Touch distribution. This document is written with the assumption that the reader is familiar with ACT-R and some sections further assume familiarity with programming in Lisp. Please refer to the ACT-R 6.0 Reference Manual for all other ACT-R issues. ACT-Touch is intended to be a long-term work in progress and therefore so is this documentation. As the software is updated this documentation will be as well to reflect the changes made to the software. Please report all errata to [Frank Tamborello](#).

ACT-Touch revision 13 has been tested with ACT-R 6.1 and found to be compatible. This version of ACT-Touch is incompatible with ACT-R 6.0. Use ACT-Touch revision 12 with ACT-R 6.0.

Acknowledgments

- Mike Byrne, Rice University
 - Public release of library code upon which ACT-Touch depends
- Dan Bothell, Carnegie Mellon University
 - ACT-R technical support
- Ross Micheals, National Institute of Standards and Technology
 - Project guidance
- NIST
 - This work is funded by Measurement Science & Engineering grant 60NANB12D134 from the National Institute of Standards and Technology in support of their Biometric Web Services project (bws.nist.gov).

Introduction

ACT-Touch is a set of manual motor request extensions for ACT-R. Facility with programming models for ACT-R is assumed throughout this document. These manual request extensions constitute theoretical claims predicting motor preparation and execution times for certain manual gestures commonly used with multitouch computer displays. These manual request extensions follow ACT-R's theoretical claims about how cognition interfaces with action to output information from the human to the environment, which in turn originated with the EPIC architecture. This document is meant as a practical guide to using ACT-Touch; it does not focus on theoretical developments.

As ACT-Touch extends ACT-R's framework with additional manual movement vocabulary, many movement styles are analogous to extant ACT-R movement styles in the sense that a movement is composed of a certain set of features which specify the movement such as a hand, a finger, a direction and a distance. Consequently ACT-Touch's movement styles are subject to the same constraints and caveats as ACT-R's, e.g., finger positions that would be physically impossible for any physical human hand to attain are specifiable for a cognitive model, and so it is up to the modeler to consider such things.

Unlike ACT-R, all distances in ACT-Touch and its virtual multitouch display are specified in pixels. The virtual multitouch display measures 1,024 pixels wide by 768 pixels tall by default. The model's default positions for its hands are at either side of the display, approximately centered vertically.

ACT-Touch is implemented as Lisp code that is meant to load with ACT-R's software. ACT-Touch can be downloaded as a single archive from Cogscent, LLC's website, <http://www.cogscent.com>. The archive contains `act-touch.lisp`, which is the set of manual request extensions; support files implementing a demonstration ACT-R device to handle ACT-Touch's manual requests; a demonstration model; and this reference manual. Direct technical support inquiries regarding ACT-Touch to Frank Tamborello at frank.tamborello@cogscent.com.

Notations in the Documentation¹

When describing the commands' syntax the following conventions will be used:

- items appearing in **bold** are to be entered verbatim
- items appearing in *italics* take user-supplied values
- items enclosed in {curly braces} are optional
- * indicates that any number of items may be supplied
- + indicates that one or more items may be supplied
- | indicates a choice between options which are enclosed in [square brackets]
- (parentheses) denote that the enclosed items are to be in a list
- a pair of items enclosed in <angle brackets> denote a cons cell with the first the car and the second the cdr
- -> indicates that calling the command on the left of the arrow will return the item to the right of the arrow
- ::= indicates that the item on the left of that symbol is of the form given by the expression on the right

When examples are provided for the commands they are shown as if they have been evaluated at a Lisp prompt. The prompt that is shown prior to the command indicates additional information about the examples. There are three types of prompts that are used in the examples:

- A prompt with just the character '>' indicates that it is an individual example – independent of those preceding or following it.
- A prompt with a number followed by '>', for example 2> means that the example is part of a sequence of calls which were evaluated and the result depends on the preceding examples. For any given sequence of calls in an example the numbering will start at 1 and increase by 1 with each new example in the sequence.
- A prompt with the letter E preceding the '>', E>, indicates that this is an example which is either incorrect or was evaluated in a context where the call results in an error or warning. This is done to show examples of the warnings and errors that can occur.

In the description of some commands it will describe a parameter or return value as a generalized boolean. What that means is that the value is used to represent a truth value – either true/successful or false/failure. If the value is the symbol **nil** then it represents false and all other values represent true. When a generalized boolean is returned by one of the commands, one should not make any assumptions about the returned value for the true case. Sometimes the true value may look like it provides additional information, but if that is not specified in the command's description then it is not guaranteed to hold for all cases or across updates to the command.

¹ Quoted from the ACT-R 6.0 Reference Manual

Loading ACT-Touch

The most straightforward way to load ACT-Touch is to simply place its files in ACT-R's user-loads folder before loading ACT-R. This will load ACT-Touch at the end of the ACT-R loading process. Load `act-touch.lisp` alone if you don't want to use the included virtual multitouch display device or demo model. However, note that whatever device you use must supply an `index-z` class slot (pixels at 72 ppi). Load `misc-lib.lisp`, `virtual-experiment-window.lisp`, and `virtual-multitouch-device.lisp` if you wish to use the included virtual multitouch display device. `Act-touch-demo-model.lisp` has an example model.

Manual Request Extensions to ACT-R

Isa tap

hand [*left* | *right*]

finger [*index* | *middle* | *ring* | *pinkie* | *thumb*]

This request will execute a tap action for the specified finger on the specified hand. This will result in the finger moving toward and momentarily contacting the surface of the multitouch display directly under the finger's current location. This is analogous to ACT-R's punch command. These are the actions which will be shown in the trace for a tap action indicating the request being received, the preparation of the features completing, the initiation time having passed, the actual contacting of the display surface which is currently under that finger (showing the global XY screen coordinates tapped by the finger on the virtual multitouch display), and the time to finish the execution of the action (returning the finger to its starting position where it is ready to act again):

```

0.050    MOTOR                TAP HAND RIGHT FINGER INDEX
...
0.200    MOTOR                PREPARATION-COMPLETE
...
0.250    MOTOR                INITIATION-COMPLETE
...
0.713    MOTOR                DEVICE-HANDLE-TAP #<MULTITOUCH-DISPLAY #x302001E3A23D>
#(500 300) RIGHT INDEX
...
0.763    MOTOR                FINISH-MOVEMENT

```

Isa tap-hold

hand [*left* | *right*]

finger [*index* | *middle* | *ring* | *pinkie* | *thumb*]

This movement style results in the model tapping and holding the specified finger on the surface of the multitouch display device until the model requests the tap-release movement style.

```

0.050    MOTOR                TAP-HOLD HAND RIGHT FINGER INDEX
...
0.200    MOTOR                PREPARATION-COMPLETE
...
0.250    MOTOR                INITIATION-COMPLETE
...
0.713    MOTOR                DEVICE-HANDLE-TAP-HOLD #<MULTITOUCH-DISPLAY
#x302001C5984D> RIGHT INDEX
Model tap-held (RIGHT INDEX).
...
0.763    MOTOR                FINISH-MOVEMENT

```


Isa tap-release

hand [*left* | *right*]

finger [*index* | *middle* | *ring* | *pinkie* | *thumb*]

When the model is already holding a finger against the surface of the multitouch display device (e.g., with a tap-hold), this movement style will release the finger from the display and return it to its default distance from the display at the current X, Y coordinates.

```

0.050    MOTOR                                TAP-RELEASE HAND RIGHT FINGER INDEX
...
0.200    MOTOR                                PREPARATION-COMPLETE
...
0.250    MOTOR                                INITIATION-COMPLETE
...
0.350    MOTOR                                DEVICE-HANDLE-TAP-RELEASE #<MULTITOUCH-DISPLAY
#x302001DD1A6D> RIGHT INDEX
Model tap-released (RIGHT INDEX).
...
0.400    MOTOR                                FINISH-MOVEMENT
```

If the model does not already have a finger on the display surface (index-z = 0), this error will result:

```

#|Warning: Finger must already be held against the surface
           of the multitouch display. |#
```

Isa swipe

hand [*left* | *right*]

finger [*index* | *middle* | *ring* | *pinkie* | *thumb*]

r *distance*

theta *direction*

num-fngers *integer*

The model moves the specified number of fingers, starting with the specified finger and incrementing from index to pinkie and thumb, onto the display and then moves the specified distance and direction, then releases the fingers from the display. Num-fngers defaults to 1.

```

0.050    MOTOR                                SWIPE HAND RIGHT FINGER INDEX R 100 THETA 1 NUM-FNGRS 3
...
0.350    MOTOR                                PREPARATION-COMPLETE
...
0.400    MOTOR                                INITIATION-COMPLETE
...
1.362    MOTOR                                DEVICE-HANDLE-SWIPE #<MULTITOUCH-DISPLAY #x302001E585ED>
#(500 300) #(554 384)
...
2.375    MOTOR                                FINISH-MOVEMENT
```

Isa pinch

hand [*left* | *right*]

finger [*index* | *middle* | *ring* | *pinkie*]

start-width *integer*

end-width *integer*

The model moves the specified finger and thumb onto the surface of the display, then moves them together or apart by the difference between the specified start- and end-widths, then releases them from the display. Start- and end-widths are in pixels.

```

0.050    MOTOR                PINCH HAND RIGHT FINGER INDEX START-WIDTH 200 END-WIDTH 0
...
0.300    MOTOR                PREPARATION-COMPLETE
...
0.350    MOTOR                INITIATION-COMPLETE
...
0.942    MOTOR                DEVICE-HANDLE-PINCH #<MULTITOUCH-DISPLAY #x302001E7E39D>
#(500 300) RIGHT INDEX 200 0
...
1.455    MOTOR                FINISH-MOVEMENT

```

Isa rotate

hand [*left* | *right*]

finger [*index* | *middle* | *ring* | *pinkie*]

rotation *direction*

This movement request results in a movement of the specified finger and the thumb to the display, moves them rotationally by the specified direction (in radians), then releases them.

```

0.050    MOTOR                ROTATE HAND RIGHT FINGER INDEX ROTATION 1
...
0.250    MOTOR                PREPARATION-COMPLETE
...
0.300    MOTOR                INITIATION-COMPLETE
...
1.153    MOTOR                DEVICE-HANDLE-ROTATE #<MULTITOUCH-DISPLAY #x302001DBB72D>
#(500 300) 36
...
1.666    MOTOR                FINISH-MOVEMENT

```

Isa move-hand-touch

[**object** *object* | **loc** *location*]

Analogous to move-cursor, this request will result in a ply-style movement of the model's right hand. That ply will move the index finger to either the object (which must be a chunk which is a subtype of visual-object) or location (which must be a chunk which is a subtype of visual-location). The trace indicates the distance and direction moved.

If the motor module's :cursor-noise parameter is bound to t , then move-hand-touch will output noisy locations with error, σ , scaled by target width, w , and off-movement-axis error also scaled by .75, according to this equation developed by May (2012) and Gallagher and Byrne (2013):

$$\sigma = \frac{w}{4.133} * \frac{\sqrt{3}}{\pi}$$

Gallagher, M. A., & Byrne, M. D. (2013). The devil is in the distribution: Refining an ACT-R model of a continuous motor task. In *Proceedings of the 12th International Conference on Cognitive Modeling*.
 May, K. (2012). *A model of error in 2D pointing tasks*. Undergraduate Honors Thesis, Rice University, Houston, TX.

...	0.100	MOTOR	MOVE-HAND-TOUCH OBJECT NIL LOC VISUAL-LOCATION0-0-0
...	0.300	MOTOR	PREPARATION-COMPLETE
...	0.350	MOTOR	INITIATION-COMPLETE
...	0.502	MOTOR	MOVE-A-HAND RIGHT 544.76416 -2.6188035
...	0.552	MOTOR	FINISH-MOVEMENT

Virtual Multitouch Display Device

The virtual multitouch display device included with ACT-Touch is a basic ACT-R device built to present a virtual visual environment to an ACT-R model and receive ACT-R's touch gesture motor movements. It includes some code that is specific to the demonstration model and one class slot that is important for ACT-Touch functionality. The index-z slot of the multitouch-display class is used for the ACT-Touch manual request extensions as a measure of distance from the model's index finger to the multitouch display surface, in pixels at 72 ppi. Whatever device is used with ACT-Touch, index-z must be supplied as a slot of the device's object class.

This section provides only superficial coverage regarding the mechanics of the device. See the ACT-R documentation for details regarding how to build your own device for ACT-R. This section includes some details about ACT-Touch's device interface methods as well as some discussion about how to modify ACT-Touch's included multitouch device. We assume familiarity with Common Lisp's object system, so object-oriented programming in Lisp will not be discussed here.

The virtual multitouch display is a slightly more sophisticated version of the list device presented in `extending-actr.pdf` distributed with ACT-R. Like the list device, it uses a paired list of visual-location and visual-object chunks as ACT-R's visual world. Unlike the list device, it uses objects of a virtual-widget class to encapsulate those chunks with data used by the experiment code to control the state of the simulated task environment and perform some action according to the appropriate device handler methods. `Virtual-multitouch-device.lisp` also contains all the device handler methods for what the experiment code should do when the model outputs each of ACT-Touch's manual request extension types. Familiarity with CLOS and ACT-R device programming are helpful for adapting or replacing the virtual multitouch display device. Both topics are covered in-depth elsewhere, namely in *ANSI Common Lisp* by Paul Graham and the *ACT-R Reference Manual*, respectively. However, this section provides basic information about ACT-Touch's virtual multitouch display device that will help you to modify it.

Device Classes

multitouch-display ()
visual-world
index-z
widgets

This class, when initialized, becomes ACT-R's device.

virtual-widget ()**nick-name****vwindow****vis-loc****vis-obj****action-type**

The virtual-widget class is a parent class to act as a container for the visual-location and visual-object chunks that comprise a model's visual environment. It also is to receive motor actions from the model so that the device can interact with the model. It may be subclassed for each style of movement (e.g., tap, swipe). The nick-name slot takes a keyword with which the experiment software may refer to that widget (e.g., :tap1). Vwindow refers to the virtual-window within which the virtual-widget appears (i.e., the virtual-multitouch-device). Vis-loc and vis-obj are the visual chunks that ACT-R will access when it constructs its visicon and the visual-location's associated visual-object. The action-type specifies the movement style the virtual-widget is to receive (e.g., tap).

Device Methods & Functions**initialize-instance :after ((wind multitouch-display) &key)**

This method sets up the multitouch-display device with its visual-location and visual-object chunks, which it uses to construct the widgets which will constitute the model's simulated world. The first subexpression within the let expression defines the visual-location chunks. The slots, such as screen-x and screen-y, determine where the widgets are placed within the ACT-R device. Change the value of the visual-location slots here to change where widgets are located and what they look like. The second subexpression defines some textual labels to appear within the device. The third subexpression defines the visual-object chunks that ACT-R's device methods will pair with each of the visual-location chunks defined for the device. The device methods (described below) determine how when ACT-R moves visual-attention to a visual-location, ACT-R gets the appropriate visual-object chunk. In this third subexpression, multitouch-display's initialize-instance after method defines these visual-object chunks.

The fourth subexpression defines the widgets that comprise the ACT-R device. There are different types of widgets, each of which correspond to the various gestures of the multitouch command vocabulary (e.g., tap, pinch). Change the first argument to change what type of widget, and thus which command, to use. This should be a symbol naming a virtual-widget subclass, such as *'tap-widget*. Each widget takes the visual-location and visual-object chunks defined in the first and third subexpressions and assigns them to widgets, interface objects to receive model input and perform some task-relevant function. These widgets take the visual-location and visual-object chunks according to the position indicated by the second argument of the *nth* expressions—e.g., (nth 0 vis-locs) refers to the first visual-location chunk. Nick-names assigned here are to correspond to states of the multitouch-display, steps of the model's task (e.g., :TAP1). This concludes the let expression.

Next, multitouch-display's initialize-instance after method sets the multitouch-display's visual-world slot to be a paired list of the visual-location and visual-object chunks and its widgets slot to be the widgets just defined. After that the method calls some model setup model functions that should be familiar to any ACT-R modelers, such as install-device and proc-display.